



## Installation Instructions for a Floor Tile Hatch.

### 1. Preparing the Opening.

Prepare an opening in the floor to fit the dimensions of the hatch.

Ensure that the edges of the opening are even and rigid.

Clean the surface of dust and debris.

### 2. Preparing the Hatch.

Try the frame in the opening to ensure it fits freely and is level.

### 3. Securing the Hatch Frame.

Install the Hatch Frame into the opening from the inside.

Align the frame with a level—the top gypsum fiberboard should be flush with the floor.

Secure the frame with temporary spacers or wedges.

Drill pilot holes from the inside of the opening through the mounting holes in the frame.

Install the anchor bolts and tighten them.

Fasten around the perimeter (see the "FASTENING" instructions in the photo).

Check the level again – there should be no distortion.

### 4. Preparing for tiling.

Before applying adhesive, coat the gypsum fiber board with waterproofing mastic.

Wait until the waterproofing mastic dries.

Apply a layer of tile adhesive.

Lay the tiles, leaving a 3-5 mm expansion joint around the perimeter of the lid.

This joint is later filled with an elastic sealant matching the color of the grout.

### 5. Final stage.

Wait until the tile adhesive and grout are completely dry.

Check that the hatch opens.

### Important:

Check the level before final tightening of the anchors.

Before applying adhesive, coat the gypsum fiberboard with waterproofing mastic.